


OKS 480 Waterproof High-Pressure Grease for Food Processing Technology



Description

OKS 480 is a fully synthetic calcium sulphonate complex grease for high loads and pressures at applications in the complete food processing technology.

Applications

- Rolling and friction bearing lubrication, even at high temperatures
- Lubrication for bearings with contact to cleaning agents or disinfectants
- For mechanical units such as levers, joints and hinges, also under strong water effect

Main fields of application

- Food processing and beverage industry
- Pharmaceutical industry
- Livestock feed industry
- Packaging industry

Advantages and benefits

- NSF H1 registered
- High shear stability prevents thinning out of the grease under extreme mechanical loads such as during vibrations
- Excellent wear protection and very good high-pressure properties
- The calcium sulphonate complex soap ensures excellent water resistance and very good corrosion protection
- Broad temperature application range (-30°C to +160°C)
- High temperature and oxidation stability through fully synthetic base oil
- Very high resistance to water-alkaline or acidic disinfectants and cleaning agents

Application tips

Clean the surfaces for optimal effect. Before filling for first time, remove anti-corrosion agent. Fill the bearing such that all functional surfaces are certain of being greased. Fill normal bearings up to about 1/3 of the free space inside the bearing. Low-speed bearings (DN value below 50,000) and their housings should be filled completely. The bearing and machine manufacturer's instructions should be observed. Subsequent lubrication at the lubrication nipples by grease gun or by automatic lubrication systems. Assess the lubrication frequency and quantity on basis of service conditions. If old grease cannot be removed, restrict the quantity of grease so as to avoid over-lubricating the bearing. If lubrication frequencies tend to be low, you should aim for a full grease change. Only mix with suitable lubricants.

Our customer advice service will be pleased to help should you have any further questions.

OKS 480 Waterproof High-Pressure Grease for Food Processing Technology

Technical Data

	Standard	Conditions	Unit	Value
Marking	Analogue to DIN 51 502			KPHC2P-30
Base oil				
Type				Polyalphaolefine
Viscosity	DIN 51 562-1	40°C	mm ² /s	100
Thickener				
Type				Calcium sulphonate complex soap
Consistency	DIN 51 818	DIN ISO 2137	NLGI grade	2
Worked penetration	DIN ISO 2137	60 cycles	0.1 mm	265-295
Drop point	ASTM D2265		°C	> 300
Application-specific data				
Density	DIN EN ISO 3838	20°C	g/cm ³	0.96
Colour				cream-coloured
DN factor			mm/min	400,000
Operating temperatures				
Lower operating temperature			°C	-30
Upper operating temperature			°C	160
Wear protection tests				
Four-ball test rig welding load	DIN 51 350-4		N	4,000
Approvals/Specifications				
Food processing technology				NSF H1 Reg. No. 148971

Packaging

- 400 ml cartridge
- 1 kg tin
- 5 kg hobbock
- 25 kg hobbock

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47
82216 Maisach, Germany

Phone: +49 (0) 8142 3051 - 523 and 556

Fax: +49 (0) 8142 3051 - 923 and 956

info@oks-germany.com

www.oks-germany.com

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress.
© = Registered trademark

Safety data sheet for industrial and commercial users is available for downloading under www.oks-germany.com.